quadax[®] VALVES SPECIFICATION FORM

INSTRUCTIONS: To begin data entry, c in Company: field. Tal advance fields. Simpl in appropriate checkb	b to y click	Contact Address Phone Email	ease check the requested face			
Face to Face Dimensions	Double Flange short pattern ISO 5752 R13 or DIN 3202 F16		Double Flange long patt ISO 5752 R14 or DIN 3		Others	
		Lug Type ANSI API 609 short	Gate Valve Replacemen ANSI B16.10	nt Buttweld Type (Schedule 80)		
		Lug Type DIN				
Body Material				Δρ		
Size			Media			
ANSI Class Switching Cycles						
Quantity _		Ambient Temperature				
nlet/Outlet Pressure		Operating Temperature				
		Pie	ase check the requested fund	tions and/or options		
Fi	unction	Normally closed	Normally opened	on/off	Control	
c	Options	With shaft extension? available with 6", 8", 12" 20", & 36"	Approval? e.g. Fire safe, BAM, TA Luft, ATEX	Special coating required? Standard: quadax specs	Further options? e.g. steam jacket	, monitoring
Test Certi	fiCates	3.1	3.2	Certificate of Origin	SIL3	Material Test Report
Order Details for Act	tuation	Bare Stem	Mounting Brackets	Gear Box	Other	
Acces	sories	Chain Wheel Operator	Padlock Flange Kit	Valve Repair Kit		
Additional Inforr	nation					



qv-VSPS 0001 Rev. 1 11/28/2018